

| Toshiba Camileo H30 - Digital Video Camera | |
|---|--|
| Image Sensor | 10 MP CMOS sensor |
| Lens | 5 x optical zoom lens (F=3,5 (W) - 3,7 (T)) |
| Focus range | Macro: 1 cm; normal: 10 cm ~ infi nite |
| LCD monitor | 3" (7,62 cm) touch-screen |
| Zoom | 4 x digital (1 x for 1080p), 5 x optical |
| Storage media | 128 MB Nand Flash Memory (usable storage: around 90 MB) |
| Expansion | SD/SDHC up to 32 GB |
| Still Picture Resolution | High: 16 MP (4608 x 3456) / standard: 10 MP (3664 x 2748) / low: 3 MP (2048 x 1536) |
| Movie resolution | FHD (1920 x 1080p / 30fps) / HD (1280 x 720p / 30fps) / WVGA (848 x 480 / 60fps) / VGA (640 x 460 / 30fps) |
| White Balance | Auto, daylight, fl uorescent, tungsten |
| Exposure | Auto |
| Self-timer | Approx. 10 sec. |
| Flash (for still) | Auto, red-eye reduction, digital light, Off |
| File format | AVI (video), JPG (image) |
| Interface | HDMI / mini USB 2.0 / TV Out |
| TV output | Digital: HDMI Analog: composite video (NTSC / PAL selectable) |
| Power saving mode | 3 minutes |
| Battery | NP120 Li-ion battery video recording time: approx. 2,5 h, (610 mA) |
| Photos taken vs. capacity (1GB SD) | 1 GB SD: 16 megapixel = 195 photos; 10 megapixel = 244 photos; 3 megapixel = 814 photos |
| Video recording vs. capacity – MPEG4 | 1 GB SD: FH (1,080p) = 15 min.; HD (720p) = 30 min.; WVGA = 25 min.; VGA = 60 min |
| System requirement | Microsoft® Windows XP / Vista / Windows 7, CPU Intel Pentium III 800 MHz above, 256 MB system memory and free 700 MB system hard disk space, 4 x CD-ROM, available USB port |
| Box content | CD (driver, manual, Arcsoft), Magix "Video Deluxe 15 Plus" Trial version (DVD), quick start guide, USB cable, video cable, HDMI cable, battery, AC adapter, hand strap, pouch (cloth bag), warranty leaflet, cleaning cloth, remote controller, lens cover |
| Certifications | CE, GOST, SASO, NCRS |
| Dimensions | 45 (W) x 65 (H) x 110 (D) mm |
| Weight | 229 g (w/o battery) |