

Toshiba Camileo X100 - Digital Video Camera	
Image Sensor	10 MP CMOS sensor
LCD monitor	3" (7,62 cm) touch-screen
Lens	10 x optical zoom lens (F=2.0 (W) - 2.8 (T))
Focus Range	Macro 1 cm; normal 10 cm ~ infinite
Zoom	10 x digital, 10 x optical
Storage media	128 MB SLC Flash Memory, 4 GB MLC Flash Memory
Expansion	SD/SDHC up to 32 GB
Still Picture Resolution	16 MP: 4608 x 3456 / 10 MP: 3644 x 2748 / 3 MP: 2048 x 1536
Movie Resolution	FHD (1920 x 1080p / 30fps), FHD (1920 x 1080i / 60fps) / HD (720p / 60fps) / HD (720p/30fps) / VGA (640 x 460 / 30fps)
White Balance	Auto, daylight, fluorescent, tungsten
Exposure	Auto
Self-Timer	Approx. 10 sec.
Flash (for Still)	Auto, red-eye reduction, digital light, Off
File Format	AVI (video), JPG (image)
Interfaces	HDMI / mini USB 2.0 / TV Out
TV Output	Digital: HDMI Analog: composite video (NTSC / PAL selectable)
Power Saving mode	3 minutes
Photo taken vs: Capacity (1GB SD)	1 GB SD: 16 megapixel = 195 photos; 10 megapixel = 244 photos; 3 megapixel = 814 photos
Video taken vs: Capacity (1GB SD)	1 GB SD: FHD (1080p / 30fps) = 12 min.; FHD (1080i / 60) = 12 min.; HD (720p / 60) = 15 min.; HD (720p / 30) = 30 min.; VGA = 60 min.
System Requirement	Microsoft® Windows XP / Vista / Windows 7, CPU Intel Pentium III 800 MHz above, 256 MB system memory and free 700 MB system hard disk space, 4 x CD-ROM, 1 available USB port
Battery	NP120 Li-ion battery video recording time: approx 2 h (860 mA)
Box content	CD (driver, manual, Arcsoft), Magix "Video Deluxe 15 Plus" Trial version (DVD), quick start guide, USB cable, video cable, HDMI cable, battery, AC adapter, hand strap, pouch, warranty leaflet, cleaning cloth, remote control, lens cover
Certifications	FCC, CE, SABS, SASO, NCRS, RoHS
Dimensions(mm)	62,30 (W) × 67,50 (H) × 122 (D) mm
Weight	270 g w/o battery